

Borealis WG341C Polypropylene

Category : Polymer , Thermoplastic , Polypropylene (PP)

Material Notes:

WG341C is a polypropylene for extrusion coating. Applications: microwave oven applications, extrusion coating of high volume production of boards and papers, coating of textile fibers, pinholes free coating, and coating of various plastic films and cellophane. Information provided by Borealis AG

Order this product through the following link:

http://www.lookpolymers.com/polymer_Borealis-WG341C-Polypropylene.php

Physical Properties	Metric	English	Comments
Density	0.910 g/cc	0.0329 lb/in ³	ISO 1183
Melt Flow	25 g/10 min @Load 2.16 kg, Temperature 230 °C	25 g/10 min @Load 4.76 lb, Temperature 446 °F	ISO 1133
Neck In	5.80 cm	2.28 in	BTM 00115
Coating Weight	>= 10.0 g/m ²	>= 6.25 lb/ream	BTM 00117

Thermal Properties	Metric	English	Comments
Vicat Softening Point	132 °C @Load 1.02 kg	270 °F @Load 2.25 lb	A50; ISO 306

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.comEmail : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China