

Bostik 6328 Low Viscosity, Long Open Time, Flexible EVA Glue Stick

Category : Polymer , Adhesive , Thermoplastic , Ethylene Vinyl Acetate , Ethylene Vinyl Acetate Copolymer (EVA), Adhesive/Sealant Grade

Material Notes:

Bostik 6328 Low Viscosity, Long Open Time, Flexible EVA Glue Stick Low viscosity. Easy to gun. Long open time. Flexible, no cracking.

Excellent bonding range.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Bostik-6328-Low-Viscosity-Long-Open-Time-Flexible-EVA-Glue-Stick.php

Physical Properties	Metric	English	Comments
Viscosity	10000 cP @Temperature 177 °C	10000 cP @Temperature 350 °F	Typical

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	66.1 °C	151 °F	
Minimum Service Temperature, Air	-30.0 °C	-22.0 °F	

Processing Properties	Metric	English	Comments
Pot Life	0.50 - 0.75 min	0.50 - 0.75 min	Open Time

Descriptive Properties	Value	Comments
Color	Straw	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China