

Braskem CP 741 Extrusion Polypropylene Heterophasic Copolymer

Category : Polymer , Thermoplastic , Polypropylene (PP) , Polypropylene, Extrusion Grade

Material Notes:

Sheet extrusion. Information provided by Braskem.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Braskem-CP-741-Extrusion-Polypropylene-Heterophasic-Copolymer.php

Physical Properties	Metric	English	Comments
Specific Gravity	0.895 g/cc	0.895 g/cc	ASTM D792
Melt Flow	0.80 g/10 min @Load 2.16 kg, Temperature 230 °C	0.80 g/10 min @Load 4.76 lb, Temperature 446 °F	ASTM D1238

Mechanical Properties	Metric	English	Comments
Hardness, Rockwell R	57	57	ASTM D785
Tensile Strength, Yield	25.0 MPa	3630 psi	ASTM D638
Elongation at Yield	17 %	17 %	ASTM D638
Flexural Modulus, 1% Secant	900 MPa	131000 psi	ASTM D790A
Izod Impact, Notched	0.370 J/cm @Temperature -20.0 °C	0.693 ft-lb/in @Temperature -4.00 °F	ASTM D256
	NB @Temperature 23.0 °C	NB @Temperature 73.4 °F	ASTM D256

Thermal Properties	Metric	English	Comments
Deflection Temperature at 0.46 MPa (66 psi)	79.0 °C	174 °F	ASTM D648

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China