

## Braskem H 107 Coating Polypropylene

Category : Polymer , Thermoplastic , Polypropylene (PP)

**Material Notes:**

Description: H 107 is a ultra-high melt flow rate additivated homopolymer used for general purposes. Designed for extrusion coating. This product exhibits excellent processability, good melt stability, as well as good transparency and gloss. Applications: Injection of thin wall pieces; Compounds; Waterproofing of raffia bags or big-bag. Information provided by Braskem

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_Braskem-H-107-Coating-Polypropylene.php](http://www.lookpolymers.com/polymer_Braskem-H-107-Coating-Polypropylene.php)

Physical Properties	Metric	English	Comments
Density	0.905 g/cc	0.0327 lb/in <sup>3</sup>	ASTM D792A
Melt Flow	80 g/10 min @Load 2.16 kg, Temperature 230 °C	80 g/10 min @Load 4.76 lb, Temperature 446 °F	ASTM D1238L

Mechanical Properties	Metric	English	Comments
Hardness, Rockwell R	100	100	ASTM D785
Tensile Strength, Yield	37.0 MPa	5370 psi	ASTM D638
Elongation at Yield	10 %	10 %	ASTM D638
Flexural Modulus	1.30 GPa	189 ksi	ASTM D790
Izod Impact, Notched	0.200 J/cm @Temperature 23.0 °C	0.375 ft-lb/in @Temperature 73.4 °F	ASTM D256A

Thermal Properties	Metric	English	Comments
Deflection Temperature at 0.46 MPa (66 psi)	93.0 °C	199 °F	ASTM D648
Deflection Temperature at 1.8 MPa (264 psi)	57.0 °C	135 °F	ASTM D648
Vicat Softening Point	153 °C	307 °F	-1kg; ASTM D1525

## Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China