

Braskem PB 601 LDPE Blow Molding Polyethylene (discontinued **)

Category : Polymer , Thermoplastic , Polyethylene (PE) , LDPE , Low Density Polyethylene (LDPE), Blow Molding Grade

Material Notes:

Applications: Toys; shrink films for pallets; general purpose; pipes and hoses; serum flasks. Information provided by Braskem

Order this product through the following link:

http://www.lookpolymers.com/polymer_Braskem-PB-601-LDPE-Blow-Molding-Polyethylene-nbspdiscontinued-.php

Physical Properties	Metric	English	Comments
Density	0.921 g/cc	0.0333 lb/in ³	ASTM D1505
Melt Flow	1.2 g/10 min @Load 2.16 kg, Temperature 230 °C	1.2 g/10 min @Load 4.76 lb, Temperature 446 °F	ASTM D1238

Mechanical Properties	Metric	English	Comments
Tensile Strength at Break	15.0 MPa	2180 psi	ASTM D638
Elongation at Break	531 %	531 %	ASTM D638

Thermal Properties	Metric	English	Comments
Vicat Softening Point	88.0 °C	190 °F	ASTM D1525

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China