

Braskem TI6500WV High Impact Copolymer Polypropylene

Category : Polymer , Thermoplastic , Polypropylene (PP) , Polypropylene Copolymer

Material Notes:

Description: High melt flow, superior low temperature impact, nucleated, good mold release, antistatic. Applications: Suggested uses include compounding, furniture, toys, packaging, large part injection molding, thin-walled injection molding. Process: Injection Molding. This resin meets the requirements for olefin polymers as defined in 21 CFR, section 177.1520 issued by the Food and Drug Administration. The additives present are covered in appropriate regulation by FDA. Information provided by Braskem

Order this product through the following link:

http://www.lookpolymers.com/polymer_Braskem-TI6500WV-High-Impact-Copolymer-Polypropylene.php

Physical Properties	Metric	English	Comments
Melt Flow	50 g/10 min @Load 2.16 kg, Temperature 230 °C	50 g/10 min @Load 4.76 lb, Temperature 446 °F	ASTM D1238

Mechanical Properties	Metric	English	Comments
Tensile Strength	20.7 MPa	3000 psi	2 in/min; ASTM D638
Elongation at Yield	5.0 %	5.0 %	2 in/min; ASTM D638
Flexural Modulus	1.17 GPa	170 ksi	0.05 in/min, 1% secant; ASTM D-790A
Izod Impact, Notched	0.694 J/cm	1.30 ft-lb/in	ASTM D256A
Impact Test	48.8 J @Temperature -29.0 °C	36.0 ft-lb @Temperature -20.2 °F	ASTM D3763

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China