

Braskem TR3350UC Random Copolymer Polypropylene

Category: Polymer, Thermoplastic, Polypropylene (PP), Polypropylene Copolymer

Material Notes:

Description: Maximum see-through clarity, minimal haze; superior color stability, process stability, and gloss; low odor, high melt flow. Applications: Suggested uses; reusable food containers, housewares, fast-cycle injection molding, packaging. Ultraclear (TM) polypropylene resin offers good clarity and performance, up to 50% improvement in haze over standard clarified products. If offers substitution opportunities versus more expensive resins such as PET, PVC, PC or PS. Process: Injection MoldingThis resin meets the requirements for olefin polymers as defined in 21 CFR, section 177.1520 issued by FDA – Food and Drugs Administration. The additives present are covered in appropriate regulation by FDA. Information provided by Braskem

Order this product through the following link:

http://www.lookpolymers.com/polymer_Braskem-TR3350UC-Random-Copolymer-Polypropylene.php

Physical Properties	Metric	English	Comments
Melt Flow	35 g/10 min	35 g/10 min	ASTM D1238
	@Load 2.16 kg, Temperature 230 °C	@Load 4.76 lb, Temperature 446 °F	

Mechanical Properties	Metric	English	Comments
Tensile Strength	31.7 MPa	4600 psi	2 in/min; ASTM D638
Elongation at Yield	13 %	13 %	2 in/min; ASTM D638
Flexural Modulus	1.17 GPa	170 ksi	0.05 in/min, 1% secant; ASTM D-790A
Izod Impact, Notched	0.427 J/cm	0.800 ft-lb/in	ASTM D256A

Optical Properties	Metric	English	Comments
Haze	5.0 %	5.0 %	50 mil Disc; ASTM D1003

Contact Songhan Plastic Technology Co.,Ltd.

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058

Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China