

Buckeye Polymers BP Flex D7030 UC85 TPO

Category : Polymer , Thermoplastic , Elastomer, TPE , Thermoplastic Olefinic Elastomer (TPO)

Material Notes:

Bumpers, Air dams TPO's are a family of thermoplastic elastomers which exhibit rubber-like properties and are processable on conventional thermoplastic equipment. These resins have excellent UV resistance and have a wide service range from -20 degrees C to 120 degrees C, high tear resistance, low density, and good paintability.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Buckeye-Polymers-BP-Flex-D7030-UC85-TPO.php

Physical Properties	Metric	English	Comments
Density	0.900 g/cc	0.0325 lb/in ³	ASTM D792
Linear Mold Shrinkage	0.010 cm/cm	0.010 in/in	ASTM D955
Melt Flow	11 g/10 min	11 g/10 min	ASTM D1238

Mechanical Properties	Metric	English	Comments
Hardness, Shore D	52	52	ASTM D2240
Tensile Strength, Ultimate	22.1 MPa	3210 psi	ASTM D638
Flexural Modulus	0.800 GPa	116 ksi	ASTM D790
Gardner Impact	NB	NB	
Tear Strength	96.4 kN/m	550 pli	ASTM D624

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China