

## Buckeye Polymers BP RPP 1310 T NAT Polypropylene, Talc Filled

Category: Polymer, Thermoplastic, Polypropylene (PP), Polypropylene with 10% Talc Filler

## **Material Notes:**

Product Information: Our Talc filled product lines exhibit excellent properties such as high stiffness, surface aesthetics, low coefficient of thermal expansion, low shrinkage, improved scratch and mar resistance, and resistance to some aggressive chemical agents. Buckeye Polymers can also customize these materials through the addition of UV packages, custom color matching, and processing additives. Product Features: Increased stiffness and heat deflectionGood UV resistanceIndustrial, appliance, construction marketsGood scratch and mar resistanceAppearance: NaturalForms: PelletsProcessing Method: Injection MoldingInformation Provided by Buckeye Polymers, Inc.

## Order this product through the following link:

http://www.lookpolymers.com/polymer\_Buckeye-Polymers-BP-RPP-1310-T-NAT-Polypropylene-Talc-Filled.php

Physical Properties	Metric	English	Comments
Specific Gravity	0.970 - 1.05 g/cc	0.970 - 1.05 g/cc	ASTM D792
Ash	11 - 16.5 %	11 - 16.5 %	ASTM D5630

Mechanical Properties	Metric	English	Comments
Tensile Strength, Yield	>= 20.10 MPa	>= 2915 psi	ASTM D638
Flexural Modulus	>= 1.900 GPa	>= 275.5 ksi	ASTM D790
Izod Impact, Notched	>= 0.288 J/cm	>= 0.540 ft-lb/in	ASTM D256

## **Contact Songhan Plastic Technology Co.,Ltd.**

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058

Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China