

Buckeye Polymers BP RPP 3015 T NAT Polypropylene, Talc Filled

Category: Polymer, Thermoplastic, Polypropylene (PP), Polypropylene with 30% Talc Filler

Material Notes:

Product Information: Our Talc filled product lines exhibit excellent properties such as high stiffness, surface aesthetics, low coefficient of thermal expansion, low shrinkage, improved scratch and mar resistance, and resistance to some aggressive chemical agents. Buckeye Polymers can also customize these materials through the addition of UV packages, custom color matching, and processing additives. Product Features: Increased stiffness and heat deflectionGood UV resistanceIndustrial, appliance, construction marketsGood scratch and mar resistanceProcessing Method: Injection MoldingInformation Provided by Buckeye Polymers, Inc.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Buckeye-Polymers-BP-RPP-3015-T-NAT-Polypropylene-Talc-Filled.php

Physical Properties	Metric	English	Comments
Melt Flow	15 - 21 g/10 min	15 - 21 g/10 min	ASTM D1238
Ash	28 - 32 %	28 - 32 %	ASTM D5630

Mechanical Properties	Metric	English	Comments
Flexural Modulus	>= 1.55 GPa	>= 225 ksi	ASTM D790
Izod Impact, Notched	>= 0.641 J/cm	>= 1.20 ft-lb/in	ASTM D256

Contact Songhan Plastic Technology Co.,Ltd.

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058 Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China