

## CIMBAR FlexTalc® 1222D Ultrafine Talc for TPO Applications, Densified

Category: Ceramic, Oxide, Silicon Oxide, Other Engineering Material, Additive/Filler for Polymer

## **Material Notes:**

Cimbar Performance Minerals' FlexTalc® products are an ultrafine talc product line specifically engineered for use in high performance TPO applications. FlexTalc® products are made by a proprietary process that results in talc products which have very high aspect ratios, are easily dispersed, provide heat aging and offer compounded color. They are available in powder and densified (D) forms. Information provided by Cimbar Performance Minerals.

Order this product through the following link:

http://www.lookpolymers.com/polymer\_CIMBAR-FlexTalc-1222D-Ultrafine-Talc-for-TPO-Applications-Densified.php

Physical Properties	Metric	English	Comments
Specific Gravity	2.78 g/cc	2.78 g/cc	
Brightness	65 %	65 %	wet
	94 %	94 %	Hunter Rd, dry
Oil Absorption	58 %	58 %	g oil/100 g filler; ASTM D281
Moisture Absorption at Equilibrium	0.50 %	0.50 %	
Loss On Ignition	7.5 %	7.5 %	
Particle Size	2.5 µm	2.5 µm	D50
	<= 11 μm	<= 11 μm	PSD 98%
pH	8.7	8.7	

Component Elements Properties	Metric	English	Comments
Al203	<= 1.0 %	<= 1.0 %	
CaO	<= 1.0 %	<= 1.0 %	
Fe2O3	<= 1.0 %	<= 1.0 %	
MgO	30 %	30 %	
SiO2	60 %	60 %	

## **Contact Songhan Plastic Technology Co.,Ltd.**

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842



Mobile: +86 13061808058

Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China