

CMW® D154F Pre-Oxidized Silver Cadmium Oxide Contact Material ASTM B781 Table 3

Category : Metal , Metal Matrix Composite , Nonferrous Metal , Precious Metal , Silver Alloy

Material Notes:

For electrical contacts; resistant to welding and high surge currents. Information provided by CMW Inc.

Order this product through the following link:

http://www.lookpolymers.com/polymer_CMW-D154F-Pre-Oxidized-Silver-Cadmium-Oxide-Contact-Material-ASTM-B781-Table-3.php

Physical Properties	Metric	English	Comments
Density	10.08 g/cc	0.3642 lb/in ³	

Mechanical Properties	Metric	English	Comments
Hardness, Rockwell F	71 - 90	71 - 90	71 (annealed) - 90 (worked)
Tensile Strength, Ultimate	276 MPa	40000 psi	Annealed
	324 MPa	47000 psi	Worked

Thermal Properties	Metric	English	Comments
Melting Point	<= 980 °C	<= 1800 °F	
Liquidus	980 °C	1800 °F	

Component Elements Properties	Metric	English	Comments
CdO	13.3 %	13.3 %	
Silver, Ag	86.7 %	86.7 %	

Electrical Properties	Metric	English	Comments
Electrical Resistivity	0.00000230 ohm-cm	0.00000230 ohm-cm	(75% IACS)

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China