

C.O.I.M. PLAXTER® P 60 Polymeric Plasticizer

Category : Other Engineering Material , Additive/Filler for Polymer , Polymer , Thermoplastic

Material Notes:

Description: Formulated with PVC, it is used for the production of fuel pipes, solvents or other oil products. Information provided by P.A.T. Products, Inc.

Order this product through the following link:

http://www.lookpolymers.com/polymer_COIM-PLAXTER-P-60-Polymeric-Plasticizer.php

Physical Properties	Metric	English	Comments
Viscosity	3500 - 4200 cP	3500 - 4200 cP	Dynamic viscosity
	@Temperature 35.0 °C	@Temperature 95.0 °F	

Mechanical Properties	Metric	English	Comments
Hardness, Shore D	65	65	
Tensile Strength, Yield	27.01 MPa	3917 psi	
Elongation at Break	283 %	283 %	
100% Modulus	0.00910 GPa	1.32 ksi	

Optical Properties	Metric	English	Comments
Gardner Color Number	2.0	2.0	

Chemical Properties	Metric	English	Comments
Acid Value	1.0	1.0	mgKOH/g

Descriptive Properties	Value	Comments
Efficiency concentration PHR	36	
N OH value (max)	5	mg KOH/g

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.comEmail : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China