

## **COR12V Cork/Neoprene Rubber Sheet**

Category: Polymer, Thermoset, Rubber or Thermoset Elastomer (TSE)

## **Material Notes:**

Description: Harvested every 9-12 years from the cork oak tree, cork is able to rebound from compression with extrusion. Applications include: stoppers, soundproofing, flooring, gaskets, and many other uses.

Order this product through the following link:

http://www.lookpolymers.com/polymer\_COR12V-CorkNeoprene-Rubber-Sheet.php

Physical Properties	Metric	English	Comments
Specific Gravity	0.850 - 0.950 g/cc	0.850 - 0.950 g/cc	

Mechanical Properties	Metric	English	Comments
Hardness, Shore A	60 - 70	60 - 70	
Tensile Strength, Yield	2.07 MPa	300 psi	No units listed, assumed to be psi.
Compression Set	>= 97.3 %	>= 97.3 %	Recovery

Descriptive Properties	Value	Comments
Flex	3 max	
Grade	Firm	

## **Contact Songhan Plastic Technology Co.,Ltd.**

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058

Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China