

Carborundum CarboTherm™ CTH40 Boron Nitride Powder

Category: Ceramic, Nitride, Other Engineering Material, Additive/Filler for Polymer

Material Notes:

Boron Nitride powders have high thermal conductivity, low dielectric loss, and low thermal expansion. They are non-abrading to electronic components, lubricious, non-toxic, and retain their dielectric properties at elevated temperatures. Applications include: use in potting compounds, encapsulants, epoxies, silicone oils and resins, and thermoplastics; use as a processing aid; use as a nucleating and foaming agent. Carborundum's CarboTherm™ powders can be custom blended to yield specific properties. Particle size and distribution can be tailored to give optimum fill and flowability while still maintaining high purity and consistency. CTH40 particles are high density agglomerates. Data provided by the manufacturer, Carborundum Corporation.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Carborundum-CarboTherm-CTH40-Boron-Nitride-Powder.php

Physical Properties	Metric	English	Comments
Apparent Bulk Density	1.00 g/cc	0.0361 lb/in³	Tap density

Component Elements Properties	Metric	English	Comments
B203	0.020 %	0.020 %	
BN	99.5 %	99.5 %	
02	0.20 %	0.20 %	includes the oxygen in B203

Contact Songhan Plastic Technology Co.,Ltd.

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058 Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China