

Cheng Yu Plastic FV30725 POM, 25% Mineral Reinforced

Category : Polymer , Thermoplastic , Acetal (POM) , Acetal Copolymer, Mineral Filled

Material Notes:

Order this product through the following link:

http://www.lookpolymers.com/polymer_Cheng-Yu-Plastic-FV30725-POM-25-Mineral-Reinforced.php

Physical Properties	Metric	English	Comments
Specific Gravity	1.35 g/cc	1.35 g/cc	ASTM D792
Linear Mold Shrinkage	0.0050 - 0.015 cm/cm	0.0050 - 0.015 in/in	ASTM D955

Mechanical Properties	Metric	English	Comments
Hardness, Rockwell M	82	82	ASTM D785
Tensile Strength, Yield	51.0 MPa	7400 psi	ASTM D638
Flexural Yield Strength	162 MPa	23500 psi	ASTM D790
Izod Impact, Notched	0.343 J/cm	0.643 ft-lb/in	ASTM D256

Thermal Properties	Metric	English	Comments
Deflection Temperature at 0.46 MPa (66 psi)	162 °C	324 °F	ASTM D648
Flammability, UL94	HB	HB	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China