

Cheng Yu Plastic IPS610BK Electric Conducting HIPS, Extrusion

Category : Polymer , Thermoplastic , Polystyrene (PS) , Polystyrene, Impact Modified

Material Notes:

Order this product through the following link:

http://www.lookpolymers.com/polymer_Cheng-Yu-Plastic-IPS610BK-Electric-Conducting-HIPS-Extrusion.php

Physical Properties	Metric	English	Comments
Specific Gravity	1.05 g/cc	1.05 g/cc	ASTM D792
Linear Mold Shrinkage	0.0030 - 0.0060 cm/cm	0.0030 - 0.0060 in/in	ASTM D955
Melt Index of Compound	6.0 - 8.0 g/10 min	6.0 - 8.0 g/10 min	ASTM D1238

Mechanical Properties	Metric	English	Comments
Hardness, Rockwell M	102	102	ASTM D785
Tensile Strength, Yield	37.4 MPa	5420 psi	ASTM D638
Flexural Yield Strength	58.8 MPa	8530 psi	ASTM D790
Izod Impact, Notched	0.883 J/cm	1.65 ft-lb/in	ASTM D256

Thermal Properties	Metric	English	Comments
Deflection Temperature at 0.46 MPa (66 psi)	78.0 °C	172 °F	ASTM D648

Electrical Properties	Metric	English	Comments
Volume Resistivity	1e+05	1e+05	ASTM D257

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China