

## Cheng Yu Plastic N6CV3 Flame Retardant Nylon 6, 30% Mineral Reinforced

Category : Polymer , Thermoplastic , Nylon , Nylon 6 , Nylon 6, 30% Mineral Filled

Material Notes:

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_Cheng-Yu-Plastic-N6CV3-Flame-Retardant-Nylon-6-30-Mineral-Reinforced.php](http://www.lookpolymers.com/polymer_Cheng-Yu-Plastic-N6CV3-Flame-Retardant-Nylon-6-30-Mineral-Reinforced.php)

Physical Properties	Metric	English	Comments
Specific Gravity	1.20 g/cc	1.20 g/cc	ASTM D792
Water Absorption	0.20 %	0.20 %	ASTM D570
Linear Mold Shrinkage	0.0080 - 0.015 cm/cm	0.0080 - 0.015 in/in	ASTM D955

Mechanical Properties	Metric	English	Comments
Hardness, Rockwell M	93	93	ASTM D785
Tensile Strength, Yield	78.5 MPa	11400 psi	ASTM D638
Flexural Yield Strength	132 MPa	19200 psi	ASTM D790
Izod Impact, Notched	0.637 J/cm	1.19 ft-lb/in	ASTM D256

Thermal Properties	Metric	English	Comments
Deflection Temperature at 0.46 MPa (66 psi)	240 °C	464 °F	ASTM D648
Flammability, UL94	V-2	V-2	

## Contact Songhan Plastic Technology Co.,Ltd.

Website : [www.lookpolymers.com](http://www.lookpolymers.com)

Email : [sales@lookpolymers.com](mailto:sales@lookpolymers.com)

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China