

Cheng Yu Plastic PP226 Flame Retardant Polypropylene, Medium Impact

Category : Polymer , Thermoplastic , Polypropylene (PP) , Polypropylene, Flame Retardant

Material Notes:

Order this product through the following link:

http://www.lookpolymers.com/polymer_Cheng-Yu-Plastic-PP226-Flame-Retardant-Polypropylene-Medium-Impact.php

Physical Properties	Metric	English	Comments
Specific Gravity	1.10 g/cc	1.10 g/cc	ASTM D792
Linear Mold Shrinkage	0.0070 - 0.015 cm/cm	0.0070 - 0.015 in/in	ASTM D955
Melt Index of Compound	20 g/10 min	20 g/10 min	ASTM D1238

Mechanical Properties	Metric	English	Comments
Hardness, Rockwell M	100	100	ASTM D785
Tensile Strength, Yield	34.3 MPa	4980 psi	ASTM D638
Flexural Yield Strength	63.7 MPa	9250 psi	ASTM D790
Izod Impact, Notched	0.422 J/cm	0.790 ft-lb/in	ASTM D256

Thermal Properties	Metric	English	Comments
Deflection Temperature at 0.46 MPa (66 psi)	136 °C	277 °F	ASTM D648
Flammability, UL94	V-0	V-0	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China