

## Cheng Yu Plastic SW15 POM/PTFE

Category : Polymer , Thermoplastic , Acetal (POM) , Acetal Copolymer, PTFE Filled

Material Notes:

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_Cheng-Yu-Plastic-SW15-POMPTFE.php](http://www.lookpolymers.com/polymer_Cheng-Yu-Plastic-SW15-POMPTFE.php)

Physical Properties	Metric	English	Comments
Specific Gravity	1.43 g/cc	1.43 g/cc	ASTM D792
Linear Mold Shrinkage	0.018 cm/cm	0.018 in/in	ASTM D955

Mechanical Properties	Metric	English	Comments
Hardness, Rockwell M	82	82	ASTM D785
Tensile Strength, Yield	56.9 MPa	8250 psi	ASTM D638
Flexural Yield Strength	90.2 MPa	13100 psi	ASTM D790
Izod Impact, Notched	0.794 J/cm	1.49 ft-lb/in	ASTM D256

Thermal Properties	Metric	English	Comments
Deflection Temperature at 0.46 MPa (66 psi)	125 °C	257 °F	ASTM D648
Flammability, UL94	HB	HB	

## Contact Songhan Plastic Technology Co.,Ltd.

Website : [www.lookpolymers.com](http://www.lookpolymers.com)Email : [sales@lookpolymers.com](mailto:sales@lookpolymers.com)

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China