

Chengdu Polyster FR2065 Flame Retardant Grade TPV

Category : Polymer , Thermoplastic , Elastomer, TPE , Thermoplastic Vulcanizate Elastomer (TPV)

Material Notes:

Good heat stability and light stability. Meets the requirements of European Dioxine Principle and the environmental protection criteria. Can be used for wires, cables, buncles, carcass of train. Information provided by Chengdu Polyster Co., Ltd.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Chengdu-Polyster-FR2065-Flame-Retardant-Grade-TPV.php

Mechanical Properties	Metric	English	Comments
Hardness, Shore A	65	65	GB 2411
Tensile Strength, Ultimate	5.00 MPa	725 psi	GB/T 528
Elongation at Break	300 %	300 %	GB/T 528
Tear Strength	14.0 kN/m	79.9 pli	GB/T 529
Tensile Set	25 %	25 %	100%; GB/T 528

Thermal Properties	Metric	English	Comments
Brittleness Temperature	<= -60.0 °C	<= -76.0 °F	GB 5470
Flammability, UL94	V-0	V-0	
Oxygen Index	25 %	25 %	GB/T 2406

Electrical Properties	Metric	English	Comments
Volume Resistivity	>= 1.00e+14 ohm-cm	>= 1.00e+14 ohm-cm	GB/T 1409
Dielectric Strength	40.0 kV/mm	1020 kV/in	GB/T 1408.1

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China