

Chevron Phillips 4516 Extrusion Coating Resin (discontinued **)

Category : Polymer , Thermoplastic , Polyethylene (PE) , LDPE , Low Density Polyethylene (LDPE), Extrusion Grade

Material Notes:

Resin Type: Homopolymer
Characteristics: Good Processability, Good MVTR, Good Heat Seal, Kosher Approved
Applications: Liquid Packaging, Cup Stock, Folding Carton, General Coating
Data provided by Chevron Chemical.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Chevron-Phillips-4516-Extrusion-Coating-Resin-nbspdiscontinued-.php

Physical Properties	Metric	English	Comments
Density	0.923 g/cc	0.0333 lb/in ³	ASTM D1505
Moisture Vapor Transmission	0.410 cc-mm/m ² -24hr-atm @Thickness 0.0254 mm, Temperature 37.8 °C	1.04 cc-mil/100 in ² -24hr-atm @Thickness 0.00100 in, Temperature 100 °F	90% RH; MIL-B-121-C
Melt Flow	3.5 g/10 min	3.5 g/10 min	ASTM D1238-62T

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China