

## Chevron Phillips MarFlex® 1010 LDPE Extrusion Coating Resin (discontinued \*\*)

Category : Polymer , Thermoplastic , Polyethylene (PE) , LDPE , Low Density Polyethylene (LDPE), Extrusion Grade

### Material Notes:

Resin Type: High Speed Resin  
Characteristics: Excellent Processability, High Temperature Extrusion Stability, Good Draw Down

Resin Applications: Food Packaging, Laminations  
Data provided by Chevron Chemical.

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_Chevron-Phillips-MarFlex-1010-LDPE-Extrusion-Coating-Resin-nbspdiscontinued-.php](http://www.lookpolymers.com/polymer_Chevron-Phillips-MarFlex-1010-LDPE-Extrusion-Coating-Resin-nbspdiscontinued-.php)

Physical Properties	Metric	English	Comments
Density	0.917 g/cc	0.0331 lb/in <sup>3</sup>	ASTM D1505-60T
Melt Flow	10 g/10 min	10 g/10 min	ASTM D1238-57T

Mechanical Properties	Metric	English	Comments
Tensile Strength, Ultimate	9.30 MPa	1350 psi	ASTM D638-61T
Tensile Strength, Yield	7.60 MPa	1100 psi	ASTM D638-61T
Elongation at Break	650 %	650 %	ASTM D638-61T

Thermal Properties	Metric	English	Comments
Vicat Softening Point	128 °C	262 °F	ASTM D1525

## Contact Songhan Plastic Technology Co.,Ltd.

Website : [www.lookpolymers.com](http://www.lookpolymers.com)

Email : [sales@lookpolymers.com](mailto:sales@lookpolymers.com)

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China