

Chevron Phillips MarFlex® 1017 General Purpose Coating Resin

Category : Polymer , Thermoplastic , Polyethylene (PE) , LDPE

Material Notes:

Characteristics: Excellent Processability, High Temperature Stability, Low Neck-in Applications: Flexible Packaging, Laminations, Sealant Resin, General Purpose Coating Resin Data provided by Chevron Chemical.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Chevron-Phillips-MarFlex-1017-General-Purpose-Coating-Resin.php

Physical Properties	Metric	English	Comments
Density	0.917 g/cc	0.0331 lb/in ³	ASTM D1505-60T
Melt Flow	7.0 g/10 min	7.0 g/10 min	ASTM D1238-57T

Mechanical Properties	Metric	English	Comments
Tensile Strength, Ultimate	13.8 MPa	2000 psi	ASTM D638
Tensile Strength, Yield	8.00 MPa	1160 psi	ASTM D638
Elongation at Break	610 %	610 %	ASTM D638

Thermal Properties	Metric	English	Comments
Vicat Softening Point	92.0 °C	198 °F	ASTM D1525

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China