

Chevron Phillips MarFlex® ER3344 Polyethylene; Masterbatch (discontinued **)

Category: Polymer, Film, Thermoplastic, Polyethylene (PE), LLDPE

Material Notes:

Metallocene polyethylene antiblock masterbatch. This erucamide slip and antiblock concentrate with its mLLDPE carrier is tailored for use with mPACT™ resins in blown film applications that require: Reduced COFMinimal antiblock effect on opticsExcellent strengthApplications: Typical blown film applications include: Use with MarFlex™ D139 and MarFlex™ D143Recommended usage is 1 to 2%May also be used with conventional LLDPEInformation provided by Phillips

Order this product through the following link:

http://www.lookpolymers.com/polymer_Chevron-Phillips-MarFlex-ER3344-Polyethylene-Masterbatch-nbspdiscontinued-.php

Physical Properties	Metric	English	Comments
Density	0.916 g/cc	0.0331 lb/in³	carrier resin value; ASTM D-1505
Melt Index of Compound	1.4 g/10 min	1.4 g/10 min	carrier resin value; ASTM D-1238
	@Load 2.16 kg, Temperature 190 °C	@Load 4.76 lb, Temperature 374 °F	
Antiblock Level	25 ppm	25 ppm	modified ASTM D-5630
Slip Level	50000 ppm	50000 ppm	modified ASTM; ASTM E-1252

Contact Songhan Plastic Technology Co.,Ltd.

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058

Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China