

Chevron Phillips Ryton® PR26 Polyphenylene Sulfide Resin (discontinued **)

Category : Polymer , Thermoplastic , Polyphenylene Sulfide (PPS) , Polyphenylene Sulfide (PPS); Molded

Material Notes:

Characteristics: Excellent thermal stabilityExcellent chemical resistanceApplications: CoatingsCompoundsExtrusionInformation provided by Chevron Phillips.Solvay Specialty Polymers has acquired the Ryton product line. This product was discontinued prior to the acquisition and is listed under the Chevron Phillips name for historical purposes.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Chevron-Phillips-Ryton-PR26-Polyphenylene-Sulfide-Resin-nbspdiscontinued-.php

| Physical Properties | Metric | English | Comments |
|---------------------|--------------------------------------|--------------------------------------|----------------|
| Particle Mesh Size | 35 Mesh | 35 Mesh | 85 wt% Passing |
| | 60 Mesh | 60 Mesh | 75 wt% Passing |
| Melt Flow | 750 g/10 min | 750 g/10 min | ASTM D1283 |
| | @Load 5.00 kg, Temperature 316 °C | @Load 11.0 lb, Temperature 600 °F | |
| Ash | 0.40 % | 0.40 % | |

| Descriptive Properties | Value | Comments |
|------------------------|-----------|----------|
| Color | Off White | |

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China