

## Chevron Phillips Ryton® PR28 Polyphenylene Sulfide Resin (discontinued \*\*)

Category : Polymer , Thermoplastic , Polyphenylene Sulfide (PPS) , Polyphenylene Sulfide (PPS) Coating Resin

### Material Notes:

Tan Color Polyphenylene Sulfide Resin Ryton® PR28 is a finely divided powder. Ryton® PPS exhibits excellent thermal stability and chemical resistance and is suitable for a variety of applications including compounds, coatings, film, and fiber. 0.4 wt % Ash. Particle size: 85 wt % passing 35 mesh. 75 wt % passing 60 mesh. Data provided by Chevron Phillips Chemical Company LP. Solvay Specialty Polymers has acquired the Ryton product line. This product was discontinued prior to the acquisition and is listed under the Chevron Phillips name for historical purposes.

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_Chevron-Phillips-Ryton-PR28-Polyphenylene-Sulfide-Resin-nbspdiscontinued-.php](http://www.lookpolymers.com/polymer_Chevron-Phillips-Ryton-PR28-Polyphenylene-Sulfide-Resin-nbspdiscontinued-.php)

Physical Properties	Metric	English	Comments
Melt Flow	350 g/10 min	350 g/10 min	Procedure B; ASTM D1283
	@Load 5.00 kg, Temperature 316 °C	@Load 11.0 lb, Temperature 601 °F	

## Contact Songhan Plastic Technology Co.,Ltd.

Website : [www.lookpolymers.com](http://www.lookpolymers.com)

Email : [sales@lookpolymers.com](mailto:sales@lookpolymers.com)

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China