

Chevron Phillips Ryton® PR33 Polyphenylene Sulfide Resin (discontinued **)

Category : Polymer , Thermoplastic , Polyphenylene Sulfide (PPS) , Polyphenylene Sulfide (PPS); Molded

Material Notes:

Characteristics: Excellent thermal stabilityExcellent chemical resistanceApplications: CoatingsCompoundsExtrusionInformation provided by Chevron Phillips.Solvay Specialty Polymers has acquired the Ryton product line. This product was discontinued prior to the acquisition and is listed under the Chevron Phillips name for historical purposes.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Chevron-Phillips-Ryton-PR33-Polyphenylene-Sulfide-Resin-nbspdiscontinued-.php

Physical Properties	Metric	English	Comments
Particle Mesh Size	35 Mesh	35 Mesh	95 wt% Passing
	60 Mesh	60 Mesh	90 wt% Passing
Melt Flow	270 g/10 min	270 g/10 min	ASTM D1283
	@Load 5.00 kg, Temperature 316 °C	@Load 11.0 lb, Temperature 600 °F	
Ash	0.70 %	0.70 %	

Descriptive Properties	Value	Comments
Color	Tan	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China