

ChevronTexaco 260 Compressor Oil

Category: Fluid, Lubricant

Material Notes:

Chevron Compressor Oil 260 is a high viscosity index lubricant for use in natural gas compressors. It is formulated from a carefully selected blend of base oils and additives that provide protection against rust, corrosion, and wear. Applications Chevron Compressor Oil 260 is used to lubricate the cylinders of reciprocating gas compressors. Chevron Compressor Oil 260 is recommended for use in:natural gas compressors such as Ariel, White Superior (Cooper), Cooper Bessemer, Energy Industries, Worthington, and Dresser Rand. dry natural gas, or natural gas containing carbon dioxide or hydrogen sulfide.

Order this product through the following link:

http://www.lookpolymers.com/polymer_ChevronTexaco-260-Compressor-Oil.php

Physical Properties	Metric	English	Comments
API Gravity	27.6 °	27.6°	
Viscosity Measurement	95	95	Viscosity Index; ASTM D2270
Saybolt Viscosity at 100°F	1380 SUS	1380 SUS	
Saybolt Viscosity at 210°F	106 SUS	106 SUS	
Kinematic Viscosity at 40°C (104°F)	260 cSt	260 cSt	ASTM D445
Kinematic Viscosity at 100°C (212°F)	20.9 cSt	20.9 cSt	ASTM D445

Thermal Properties	Metric	English	Comments
Pour Point	-16.0 °C	3.20 °F	ASTM D97
Flash Point	275 °C	527 °F	ASTM D92

Component Elements Properties	Metric	English	Comments	
Calcium, Ca	0.078 %	0.078 %		

Descriptive Properties	Value	Comments
Color	4.5	

Contact Songhan Plastic Technology Co.,Ltd.

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058



Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China