

ChevronTexaco 8-T White Oil

Category: Fluid, Lubricant, White Mineral Oil (WMO)

Material Notes:

FeaturesChevron White Oils are technical grade oils processed from paraffinic oil. Mixtures of paraffinic and naphthenic hydrocarbons, they are virtually free of nitrogen, sulfur, oxygen, and aromatic compounds. They approach the quality requirements of food grade white oils. Applications Chevron White Oils are used in food packaging or handling applications such as:process oilsplaticizers dust control oils or moisture barriers in aniumal feed manufacturelubricants on machinery of in food packaging such as foilrust preventative formulations for food handling defoamers Chevron White Oils ar recommended for applications where discoloration, staining, or sludging in service must be minimized. In applications whre higher temperatures are encountered, such as heating baths or lubricants, greatly extended service life is usually noted when Chevron White Oils, in combination with an antioxidant, are substituted for ordinary mineral oils.

Order this product through the following link:

http://www.lookpolymers.com/polymer_ChevronTexaco-8-T-White-Oil.php

Physical Properties	Metric	English	Comments
API Gravity	34.2°	34.2°	
Saybolt Viscosity at 100°F	86 SUS	86 SUS	
Kinematic Viscosity at 40°C (104°F)	15.8 cSt	15.8 cSt	ASTM D445

Thermal Properties	Metric	English	Comments
Pour Point	-12.0 °C	10.4 °F	ASTM D97
Flash Point	182 °C	360 °F	ASTM D92

Descriptive Properties	Value	Comments
Color	+25, Saybolt	

Contact Songhan Plastic Technology Co.,Ltd.

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058

Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China