

ChevronTexaco 904 Grease NLGI Grade 1/2

Category: Fluid, Lubricant, Calcium Gellant

Material Notes:

Texaco 904 Grease is a calcium soap grease. It contains graphite which enhances its lubricity. Typical test data are average values only.

Minor variations which do not affect product performance are to be expected in normal manufacturing. Notes: Minimum operating temperature is the lowest temperature at which a grease, already in place, could be expected to provide lubrication. Most greases cannot be pumped at these minimum temperatures. Maximum operating temperature is the highest temperature at which the grease could be used with frequent (daily) relubrication. Determined on mineral oil extracted by vacuum filtration. CPS Number: 222314; MSDS Number: 9001

Order this product through the following link:

http://www.lookpolymers.com/polymer_ChevronTexaco-904-Grease-NLGI-Grade-12.php

| Physical Properties | Metric | English | Comments |
|--------------------------------------|----------|----------|------------------------------|
| Solids Content | 12 % | 12 % | |
| Viscosity Measurement | 72 | 72 | Viscosity Index, See Note 3. |
| Saybolt Viscosity at 100°F | 394 SUS | 394 SUS | See Note 3. |
| Saybolt Viscosity at 210°F | 54 SUS | 54 SUS | See Note 3. |
| Kinematic Viscosity at 40°C (104°F) | 75.3 cSt | 75.3 cSt | See Note 3. |
| Kinematic Viscosity at 100°C (212°F) | 8.4 cSt | 8.4 cSt | See Note 3. |

| Mechanical Properties | Metric | English | Comments |
|----------------------------|--------|---------|-------------------------------------|
| Penetration P(60), 1/10 mm | 340 | 340 | Unknown Amount of Work, 25°C (77°F) |

| Thermal Properties | Metric | English | Comments |
|----------------------------------|----------|----------|-------------|
| Maximum Service Temperature, Air | 78.0 °C | 172 °F | See Note 2. |
| Minimum Service Temperature, Air | -23.0 °C | -9.40 °F | See Note 1. |
| Flash Point | 172 °C | 342 °F | See Note 3. |
| Dropping Point | 99.0 °C | 210 °F | |

| Descriptive Properties | Value | Comments |
|------------------------|--------|----------|
| Color | Black | |
| Texture | Smooth | |
| Thickener, % | 10 | Calcium |



Contact Songhan Plastic Technology Co.,Ltd.

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058

Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China