

ChevronTexaco AFP White Oil

Category: Fluid, Lubricant, White Mineral Oil (WMO)

Material Notes:

Chevron White Oil AFP is a technical grade white oil processed from paraffinic oil Applications Chevron White Oil AFP's major application is the dedusting of animal feeds and the preparation of animal feed cubes and pellets. Other applications for Chevron White Oil AFP include: defoamermold release lubricant component in the manufacture of plastic food containers

Order this product through the following link:

http://www.lookpolymers.com/polymer_ChevronTexaco-AFP-White-Oil.php

Physical Properties	Metric	English	Comments
API Gravity	36°	36°	
Saybolt Viscosity at 100°F	72 SUS	72 SUS	
Kinematic Viscosity at 40°C (104°F)	13.2 cSt	13.2 cSt	ASTM D445

Thermal Properties	Metric	English	Comments
Pour Point	-12.0 °C	10.4 °F	ASTM D97
Flash Point	182 °C	360 °F	ASTM D92

Descriptive Properties	Value	Comments
Color	+25, Saybolt	

Contact Songhan Plastic Technology Co.,Ltd.

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058

Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China