

## ChevronTexaco Aerosol Open Gear Grease

Category : Fluid , Lubricant

**Material Notes:**

Features Chevron Open Gear Greases are formulated with high viscosity mineral oils in a nonsoap-based thickener. These greases appear brownish-black and are extremely tacky. Chevron Open Gear Greases contain special functional fillers such as molybdenum disulfide and graphite, which impart a long-lasting film on working surfaces. They also contain tackiness additives, wetting agents and rust inhibitors to protect metal surfaces. None of the Chevron Open Gear Greases contain chlorinated solvents. Chevron Open Gear Greases have been formulated with a diluent that does not require a cancer warning label. Chevron Open Gear Greases are in every sense true greases and not asphalt-based open gear lubricants. This has a number of advantages. The lubricants can carry a more complete additive system including friction modifiers such as molybdenum disulfide and graphite, which apply a long lasting antiwear film on gear teeth. Applications Chevron Open Gear Greases are recommended: for all open gears in industrial, mining, construction, and marine equipment for chain and sprocket lubrication as a tenacious fifth wheel lubricant. Chevron Open Gear Greases can be applied in a variety of methods, including: from a cartridge in a caulking gun from an aerosol can for easy application in hard-to-reach lubrication points through a mechanical lubricator over a wide range of operating temperatures

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_ChevronTexaco-Aerosol-Open-Gear-Grease.php](http://www.lookpolymers.com/polymer_ChevronTexaco-Aerosol-Open-Gear-Grease.php)

| Physical Properties                  | Metric   | English  | Comments  |
|--------------------------------------|----------|----------|-----------|
| Kinematic Viscosity at 40°C (104°F)  | 6532 cSt | 6532 cSt | ASTM D445 |
| Kinematic Viscosity at 100°C (212°F) | 152 cSt  | 152 cSt  | ASTM D445 |

| Mechanical Properties                 | Metric   | English       | Comments |
|---------------------------------------|----------|---------------|----------|
| Four Ball Extreme Pressure, Weld Load | 315 kg   | 695 lb (mass) |          |
| Four Ball Wear                        | 0.600 mm | 0.0236 in     |          |

| Descriptive Properties           | Value       | Comments |
|----------------------------------|-------------|----------|
| Color                            | Brown-Black |          |
| Lincoln Ventmeter, at 400psi, °C | -29         |          |
| Resultant Film                   | Tacky       |          |
| Rust Test, ASTM D1743, rating    | Pass        |          |
| Texture                          | Smooth      |          |
| Thickener, % / type              | Nonsoap     |          |

**Contact Songhan Plastic Technology Co.,Ltd.**

Website : [www.lookpolymers.com](http://www.lookpolymers.com)

Email : [sales@lookpolymers.com](mailto:sales@lookpolymers.com)

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China