

ChevronTexaco CP Grease

Category : Fluid , Lubricant , Lithium Gellant

Material Notes:

FeaturesChevron CP Grease is a corrosion preventive grease.It is manufactured with a special low viscosity, low pour point base oil, a lithium thickener, and rust and oxidation inhibitors. It is light green in color with a smooth texture.Chevron CP Grease’s soft consistency and very low oil pour point, -40°C (-40°F), enables it to provide excellent lubrication and easy application at low ambient temperatures.Chevron CP Grease provides excellent corrosion protection. It stays on metal surfaces, protects bearings from moisture, and leaves a protective coating when equipment is not in use. In equipment such as cotton pickers, it resists the corrosive action of plant juices and does not leak or splash on cotton.**Applications**Chevron CP Grease is specifically recommended for John Deere, IHC-McCormick, and Case mechanical cotton pickers.It is also recommended for other agricultural or industrial applications calling for a low consistency product with low operating temperature properties. Chevron CP Grease is an excellent preservative grease for parts kept in storage.Chevron CP Grease NLGI 00 meets or exceeds the requirements of obsolete John Deere JDN 305 and JDN 360 standards for Cotton Picker Spindle Lubricants.

Order this product through the following link:

http://www.lookpolymers.com/polymer_ChevronTexaco-CP-Grease.php

Physical Properties	Metric	English	Comments
Viscosity Measurement	10	10	Viscosity Index; ASTM D2270
Saybolt Viscosity at 100°F	131 SUS	131 SUS	
Saybolt Viscosity at 210°F	40 SUS	40 SUS	
Kinematic Viscosity at 40°C (104°F)	25 cSt	25 cSt	ASTM D445
Kinematic Viscosity at 100°C (212°F)	4.0 cSt	4.0 cSt	ASTM D445

Mechanical Properties	Metric	English	Comments
Penetration	415	415	Worked (60 strokes)
Penetration P(0), 1/10 mm	415	415	

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	80.0 °C	176 °F	
Minimum Service Temperature, Air	-35.0 °C	-31.0 °F	
Pour Point	-40.0 °C	-40.0 °F	ASTM D97
Flash Point	168 °C	334 °F	ASTM D92
Dropping Point	162 °C	324 °F	

Descriptive Properties	Value	Comments
Color	Light Green	
Texture	Smooth	
Thickener, % / type	3.5 / Lithium	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China