

ChevronTexaco Cepheus® 220

Category: Fluid, Lubricant

Material Notes:

Texaco Cepheus oil deliver value throughThe ability to retain lubrication properties in the presence of water. Good rust protection from a carefully designed additive package. The ease with which they can be washed off textiles Texaco Cepheus oils are naphthenic based oils compounded with fatty oils. They protect well against rusting and feed line plugging. Texaco Cepheus oils are suitable for lubricating bearings and other machine parts of textile machines are well as other industrial equipment needing lightly compounded lubricants Texaco Cepheus 150 and 220 are recommended for air compressor applications where there is the possibility of carbon buildup or where there is significant moisture. Do not use in breathing air apparatus or medical equipment. Typical test data are average values only. Minor variations which do not affect product performance are to be expected in normal manufacturing. CPS Number: 222777; MSDS Number: 8958

Order this product through the following link:

http://www.lookpolymers.com/polymer_ChevronTexaco-Cepheus-220.php

Physical Properties	Metric	English	Comments
API Gravity	20.5°	20.5°	
Viscosity Measurement	10	10	Viscosity Index
Saybolt Viscosity at 100°F	1135 SUS	1135 SUS	
Saybolt Viscosity at 210°F	70.3 SUS	70.3 SUS	
Kinematic Viscosity at 40°C (104°F)	209 cSt	209 cSt	
Kinematic Viscosity at 100°C (212°F)	12.6 cSt	12.6 cSt	

Thermal Properties	Metric	English	Comments
Pour Point	-20.0 °C	-4.00 °F	
Flash Point	218 °C	424 °F	

Descriptive Properties	Value	Comments
Fatty Oil wt %	3	

Contact Songhan Plastic Technology Co.,Ltd.

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058

Skype: lookpolymers



Address: United North Road 215, Fengxian District, Shanghai City, China