

ChevronTexaco Cetus® DE 32

Category : Fluid , Lubricant

Material Notes:

Texaco Cetus DE oils deliver value through: Long life — Texaco Cetus DE oils have a low sludge-forming tendency and a high solvency for deposits that help to keep compressor parts clean. Their ability to reduce oil consumption and carry over; reduce varnish, sludge, and deposits; as well as increase deposit-free valve life translates to reducing compressor maintenance and energy costs. Ignition safety — Texaco Cetus DE oils provide a greater margin of safety than conventional petroleum products because their flash points, fire points, and auto ignition temperatures are much higher. They are not, however, true fire resistant fluids. Texaco Cetus DE oils are synthetic diester-based, oxidation resistant, compressor oils. Texaco Cetus DE oils are used for portable and stationary rotary screw, rotary vane, and reciprocating compressors. While specific manufacturer recommendations vary, the ISO 68 grade is most commonly used for rotary compressors, while higher viscosity grades are preferred for reciprocating units. These oils can be used in compressors with the following gases: process air, benzene, butadiene, carbon dioxide (dry), carbon monoxide, ethylene, furnace (crack) gas, helium, hydrocarbon gases, hydrogen, inert gases, methane, natural gas, nitrogen, propane, sulfur hexafluoride, and synthesis gas. Texaco Cetus DE oils can be used in contact with the following seals, paints, and plastics: Viton®1, High nitrile Buna N, Teflon®2, Epoxy paint, Oil-resistant alkyd, Nylon, Delrin®3, Celcon®4, These oils should not be used with: Neoprene, SBR rubber, Low nitrile Buna N, Acrylic paint, Lacquer, Polystyrene, PVC, ABS. Do not use in breathing air apparatus or medical equipment. Typical test data are average values only. Minor variations which do not affect product performance are to be expected in normal manufacturing. CPS Number: 222077; MSDS Number: 8713

Order this product through the following link:

http://www.lookpolymers.com/polymer_ChevronTexaco-Cetus-DE-32.php

Physical Properties	Metric	English	Comments
API Gravity	22.6 °	22.6 °	
Viscosity Measurement	131	131	Viscosity Index
Saybolt Viscosity at 100°F	144 SUS	144 SUS	
Saybolt Viscosity at 210°F	44.3 SUS	44.3 SUS	
Kinematic Viscosity at 40°C (104°F)	28 cSt	28 cSt	
Kinematic Viscosity at 100°C (212°F)	5.4 cSt	5.4 cSt	

Thermal Properties	Metric	English	Comments
Pour Point	-56.0 °C	-68.8 °F	
Flash Point	258 °C	496 °F	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.comEmail : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China