

## ChevronTexaco Delo® 1000 Marine Engine Oil, SAE 40

Category : Fluid , Lubricant

### Material Notes:

**Features** Chevron Marine Engine Oils Delo 1000 Marine are high quality engine oils developed for use in a wide variety of medium speed trunk piston engines, including the latest design high output engines burning marine diesel oils. They are manufactured using high quality base oils and dispersant, detergent, antioxidant, antiwear, and alkaline reserve additives. The base number or alkalinity of these oils is 12. The detergent/dispersant properties of these oils provide exceptionally clean crankcases and keep oil control rings clean. These properties reduce lube oil filter blockage and provide excellent insolubles control handling characteristics. Chevron Marine Engine Oils Delo 1000 Marine have extremely good viscosity control in severe high temperature service. They have a high degree of water tolerance. Water can be centrifuged out with essentially no loss of additive. Water washing of the oil, however, is not recommended. **Applications** Chevron Marine Engine Oils Delo 1000 Marine are recommended for use in medium speed trunk piston engines burning marine diesel oils with a sulfur content of up to 1.5%. They are also recommended for air compressor lubrication. The antiwear additives contained in Chevron Marine Engine Oils Delo 1000 Marine provide outstanding load carrying and antiwear characteristics. In the FZG (A/8, 3/90) gear test, the fail stage for Chevron Marine Engine Oil Delo 1000 Marine was Stage 11. The FZG values permit these oils to be used in engine reduction gears and other applications where additional EP/ antiwear properties are required. Chevron Marine Engine Oil Delo 1000 SAE 50 is intended to be used for running-in purposes in crosshead diesel engines. Chevron Marine Engine Oils Delo 1000 Marine meet the requirements of API Service Category CF. They are approved by all major engine manufacturers for use in their medium speed engines.

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_ChevronTexaco-Delo-1000-Marine-Engine-Oil-SAE-40.php](http://www.lookpolymers.com/polymer_ChevronTexaco-Delo-1000-Marine-Engine-Oil-SAE-40.php)

Physical Properties	Metric	English	Comments
API Gravity	24.5 °	24.5 °	
Viscosity Measurement	98	98	Viscosity Index; ASTM D2270
Kinematic Viscosity at 40°C (104°F)	145 cSt	145 cSt	ASTM D445
Kinematic Viscosity at 100°C (212°F)	14.4 cSt	14.4 cSt	ASTM D445
Ash	1.67 %	1.67 %	Sulfated Ash wt%

Thermal Properties	Metric	English	Comments
Pour Point	-15.0 °C	5.00 °F	ASTM D97
Flash Point	245 °C	473 °F	ASTM D92

Component Elements Properties	Metric	English	Comments
Phosphorous, P	0.046 %	0.046 %	
Zinc, Zn	0.056 %	0.056 %	

Chemical Properties	Metric	English	Comments
Total Base Number	12	12	ASTM D2896

**Contact Songhan Plastic Technology Co.,Ltd.**

Website : [www.lookpolymers.com](http://www.lookpolymers.com)  
Email : [sales@lookpolymers.com](mailto:sales@lookpolymers.com)  
Tel : +86 021-51131842  
Mobile : +86 13061808058  
Skype : lookpolymers  
Address : United North Road 215,Fengxian District, Shanghai City,China