

ChevronTexaco Delo® 3000 Marine Engine Oil, SAE 30

Category : Fluid , Lubricant

Material Notes:

FeaturesChevron Marine Engine Oil Delo 3000 Marine is a high quality engine oils developed for use in a wide variety of medium speed trunk piston engines burning residual fuels.It is manufactured using high quality base oils and dispersant, detergent, antioxidant, antiwear, and alkaline reserve additives.The base number or alkalinity of this oil is 30. The detergent/dispersant properties of this oil provides exceptionally clean crankcases and keep oil control rings clean. These properties reduce lube oil filter blockage and provide excellent insolubles control handling characteristics.Chevron Marine Engine Oil 3000 Marine has extremely good viscosity control in severe high temperature service.It has a high degree of water tolerance. Water can be centrifuged out with essentially no loss of additive. Water washing of the oil, however, is not recommended.**Applications**Chevron Marine Engine Oil Delo 3000 Marine is recommended for use in medium speed trunk piston engines burning residual fuels with up to 3.5% sulfur content.The antiwear additives contained in Chevron Marine Engine Oil Delo 3000 Marine provide outstanding load carrying and antiwear characteristics. In the FZG (A/8, 3/90) gear test, the fail stage for Chevron Marine Engine Oil Delo 3000 Marine was Stage 10. The FZG values permit this oil to be used in engine reduction gears and other applications where additional EP/ antiwear properties are required.Chevron Marine Engine Oil Delo 3000 Marine meets the requirements of API Service Category CF. It is approved by all major engine manufacturers for use in their medium speed engines.

Order this product through the following link:

http://www.lookpolymers.com/polymer_ChevronTexaco-Delo-3000-Marine-Engine-Oil-SAE-30.php

Physical Properties	Metric	English	Comments
API Gravity	27.4 °	27.4 °	
Viscosity Measurement	99	99	Viscosity Index; ASTM D2270
Kinematic Viscosity at 40°C (104°F)	108 cSt	108 cSt	ASTM D445
Kinematic Viscosity at 100°C (212°F)	11.9 cSt	11.9 cSt	ASTM D445
Ash	3.95 %	3.95 %	Sulfated Ash wt%

Thermal Properties	Metric	English	Comments
Pour Point	-21.0 °C	-5.80 °F	ASTM D97
Flash Point	245 °C	473 °F	ASTM D92

Component Elements Properties	Metric	English	Comments
Phosphorous, P	0.046 %	0.046 %	
Zinc, Zn	0.056 %	0.056 %	

Chemical Properties	Metric	English	Comments
Total Base Number	30	30	ASTM D2896

Chemical Properties

Metric

English

Comments

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China