

## ChevronTexaco Delo® 3000 Marine Engine Oil, SAE 40

Category : Fluid , Lubricant

### Material Notes:

**Features** Chevron Marine Engine Oil Delo 3000 Marine is a high quality engine oils developed for use in a wide variety of medium speed trunk piston engines burning residual fuels. It is manufactured using high quality base oils and dispersant, detergent, antioxidant, antiwear, and alkaline reserve additives. The base number or alkalinity of this oil is 30. The detergent/dispersant properties of this oil provides exceptionally clean crankcases and keep oil control rings clean. These properties reduce lube oil filter blockage and provide excellent insolubles control handling characteristics. Chevron Marine Engine Oil 3000 Marine has extremely good viscosity control in severe high temperature service. It has a high degree of water tolerance. Water can be centrifuged out with essentially no loss of additive. Water washing of the oil, however, is not recommended. **Applications** Chevron Marine Engine Oil Delo 3000 Marine is recommended for use in medium speed trunk piston engines burning residual fuels with up to 3.5% sulfur content. The antiwear additives contained in Chevron Marine Engine Oil Delo 3000 Marine provide outstanding load carrying and antiwear characteristics. In the FZG (A/8, 3/90) gear test, the fail stage for Chevron Marine Engine Oil Delo 3000 Marine was Stage 10. The FZG values permit this oil to be used in engine reduction gears and other applications where additional EP/ antiwear properties are required. Chevron Marine Engine Oil Delo 3000 Marine meets the requirements of API Service Category CF. It is approved by all major engine manufacturers for use in their medium speed engines.

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_ChevronTexaco-Delo-3000-Marine-Engine-Oil-SAE-40.php](http://www.lookpolymers.com/polymer_ChevronTexaco-Delo-3000-Marine-Engine-Oil-SAE-40.php)

| Physical Properties                  | Metric   | English  | Comments                    |
|--------------------------------------|----------|----------|-----------------------------|
| API Gravity                          | 23.8 °   | 23.8 °   |                             |
| Viscosity Measurement                | 100      | 100      | Viscosity Index; ASTM D2270 |
| Kinematic Viscosity at 40°C (104°F)  | 143 cSt  | 143 cSt  | ASTM D445                   |
| Kinematic Viscosity at 100°C (212°F) | 14.4 cSt | 14.4 cSt | ASTM D445                   |
| Ash                                  | 3.95 %   | 3.95 %   | Sulfated Ash wt%            |

| Thermal Properties | Metric   | English | Comments |
|--------------------|----------|---------|----------|
| Pour Point         | -15.0 °C | 5.00 °F | ASTM D97 |
| Flash Point        | 250 °C   | 482 °F  | ASTM D92 |

| Component Elements Properties | Metric  | English | Comments |
|-------------------------------|---------|---------|----------|
| Phosphorous, P                | 0.046 % | 0.046 % |          |
| Zinc, Zn                      | 0.056 % | 0.056 % |          |

| Chemical Properties | Metric | English | Comments   |
|---------------------|--------|---------|------------|
| Total Base Number   | 30     | 30      | ASTM D2896 |

Chemical Properties

Metric

English

Comments

## Contact Songhan Plastic Technology Co.,Ltd.

Website : [www.lookpolymers.com](http://www.lookpolymers.com)

Email : [sales@lookpolymers.com](mailto:sales@lookpolymers.com)

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China