

ChevronTexaco Delo® 400 SAE 30

Category : Fluid , Lubricant

Material Notes:

Chevron Delo 400 heavy duty motor oils are exceptional, super premium quality "universal" engine oils which exceed industry and engine manufacturers' performance requirements. They are formulated utilizing the most advanced additive technology available to provide outstanding engine protection under both pre- and post-1998 EPA standards for exhaust particulate emissions for on highway diesel trucks, using both high and low sulfur diesel fuels. Chevron Delo 400 SAE 10W, 20, 30, 40 and 50 are manufactured using carefully selected premium paraffinic base oils and an optimal blend of the latest technology in dispersant, detergent, oxidation inhibition, anti-wear, corrosion inhibition, and defoaming additives. Chevron Delo 400 SAE 10W-30 is formulated with ISO-SYN™ base stocks. Applications: Chevron Delo 400 oils are mixed-fleet motor oils recommended for all four-stroke gasoline diesel engines operating under severe service and subjected to wide variations in climactic conditions. Chevron Delo 400 oils are excellent for use in new advanced engines developed in response to 1998 lower exhaust particulate emissions with features such as four-valve heads, turbo charging, retarded fuel injections timing, direct injection, shorter piston crowns, higher power density, peak firing pressures up and beyond 2300 psi, intercooling, full electronic management of fuel systems, and exhaust particulate traps. Chevron Delo 400 oils are also formulated for superior performance in older engines using both normal, high and low sulfur diesel fuels. Chevron Delo 400 oils are not recommended for use in DDC two-stroke engines. Chevron Delo 400 SAE 30 can be used in in powershift transmissions requiring Caterpillar TO 2 or an Allison C4 fluid. Chevron Delo 400 SAE 10W, 20, 30, and 40 are authorized by USDA for use in federally inspected meat and poultry plants as H2 lubricants with no food contact.

Order this product through the following link:

http://www.lookpolymers.com/polymer_ChevronTexaco-Delo-400-SAE-30.php

Physical Properties	Metric	English	Comments
API Gravity	29 °	29 °	
Viscosity Measurement	104	104	Viscosity Index; ASTM D2270
Kinematic Viscosity at 40°C (104°F)	105 cSt	105 cSt	ASTM D445
Kinematic Viscosity at 100°C (212°F)	12.1 cSt	12.1 cSt	ASTM D445
Ash	1.35 %	1.35 %	Sulfated Ash wt%

Thermal Properties	Metric	English	Comments
Pour Point	-31.0 °C	-23.8 °F	ASTM D97
Flash Point	242 °C	468 °F	ASTM D92

Component Elements Properties	Metric	English	Comments
Phosphorous, P	0.116 %	0.116 %	
Zinc, Zn	0.127 %	0.127 %	

Chemical Properties	Metric	English	Comments
Total Base Number	10.2	10.2	ASTM D2896

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China