

ChevronTexaco Delo® 400 Synthetic, SAE 0W-30

Category : Fluid , Lubricant

Material Notes:

Chevron Delo 400 Synthetic heavy duty motor oils are multipurpose 100% synthetic lubricants formulated for use in gasoline and diesel engines, torque converters, gear cases, and hydraulic systems operating in subzero arctic-type temperatures. They are manufactured using stable synthetic base stocks. These oils utilize highly dispersed viscosity index improvers that promote stable viscosities and soot dispersancy between oil drains. Applications: Chevron Delo 400 Synthetic heavy duty motor oils are recommended for use in diesel and four-stroke cycle gasoline engines, torque converters, gear cases, and hydraulic systems operating year-round in arctic-type climates. They utilize the latest technology to provide excellent performance with either high or low sulfur diesel fuels. Chevron Delo 400 Synthetic heavy duty motor oils meet: API Service Categories: CG-4, CF, CD, SH, SJ, Energy Conserving for API SH (SAE 0W-30), CI-4 (SAE 5W-40) Major diesel engine manufacturers requirements: Mack EO-M PLUS, EO-M (SAE 5W-40), Cummins CES 20076, 20071 (SAE 5W-40) Performance requirements of: Allison C4 (SAE 0W-30) Manufacturers performance requirements: Ford ESE-M2C153-E, General Motors GM 6094-M

Order this product through the following link:

http://www.lookpolymers.com/polymer_ChevronTexaco-Delo-400-Synthetic-SAE-0W-30.php

Physical Properties	Metric	English	Comments
API Gravity	33.1 °	33.1 °	
Viscosity	2780 cP @Temperature -30.0 °C	2780 cP @Temperature -22.0 °F	Cold Crank
Viscosity Measurement	190	190	Viscosity Index; ASTM D2270
Kinematic Viscosity at 40°C (104°F)	52.2 cSt	52.2 cSt	ASTM D445
Kinematic Viscosity at 100°C (212°F)	10.3 cSt	10.3 cSt	ASTM D445
Ash	1.1 %	1.1 %	Sulfated Ash wt%

Thermal Properties	Metric	English	Comments
Pour Point	-60.0 °C	-76.0 °F	ASTM D97
Flash Point	215 °C	419 °F	ASTM D92

Component Elements Properties	Metric	English	Comments
Phosphorous, P	0.114 %	0.114 %	
Zinc, Zn	0.13 %	0.13 %	

Chemical Properties	Metric	English	Comments
Total Base Number	10	10	ASTM D2896

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China