

## ChevronTexaco Delo® 6170 CFO Diesel Engine Oil, SAE 20W-40

Category: Fluid, Lubricant

## **Material Notes:**

FeaturesChevron Diesel Engine Oils Delo 6170 CFO are outstanding high dispersancy, high alkalinity, 17 base number engine oils for use in diesel engines used in railroad, power generation, oil well drilling, and marine and industrial service requiring a zinc-free oil and Generation 4 LL or Generation 5 lubricant characteristics. Chevron Diesel Engine Oils Delo 6170 CFO represent the latest in oil technology for this type of service and satisfy the requirements of the newest engine technology. Chevron Diesel Engine Oils Delo 6170 CFO are manufactured using the highest quality base oils and a nonchlorinated additive package that offers low engine wear and minimizes used oil disposal issues. Chevron Diesel Engine Oils Delo 6170 CFO SAE 20W-40 includes a dispersant viscosity index improver. New engine designs, aimed at reducing operating expenses, operate at higher combustion pressures and higher temperatures which require improved oxidation and viscosity control. In addition, new piston and ring designs call for increased alkalinity reserve to control corrosive wear and deposit formation. Chevron Diesel Engine Oils Delo 6170 CFO successfully handle these new requirements by providing outstanding resistance to viscosity increase due to superior oxidation and thermal stability, and by providing a high alkalinity level (17 base number, ASTM D 2896). Applications Chevron Diesel Engine Oils Delo 6170 CFO are recommended: for use in all railroad-type diesel engines for locomotive, marine equipment, stationary electric generating plants, offshore drilling equipment, and many other applications. where large mediumspeed EMD or GE diesel engines are used for primary power. Chevron Diesel Engine Oils Delo 6170 CFO are: completely compatible with earlier Delo railroad oils.miscible with competitive railroad type oils and additive systems consistent with engine manufacturers recommended practices. Chevron Diesel Engine Oils Delo 6170 CFO provide excellent performance in older locomotive types such as Sulzer, Baldwin, and ALCO. Chevron Diesel Engine Oil Delo 6170 CFO SAE 40 is recommended for use in Caterpillar and other diesel engines operating where sulfated ash levels above 1% are acceptable.where DDC engines are used for auxiliary power.Detroit Diesel Corporation approves the use of Generation 4 and 5 zinc-free railroad engine oils in these applications.

## Order this product through the following link:

http://www.lookpolymers.com/polymer\_ChevronTexaco-Delo-6170-CFO-Diesel-Engine-Oil-SAE-20W-40.php

| Physical Properties                  | Metric   | English  | Comments                    |
|--------------------------------------|----------|----------|-----------------------------|
| API Gravity                          | 28°      | 28°      |                             |
| Viscosity Measurement                | 115      | 115      | Viscosity Index; ASTM D2270 |
| Kinematic Viscosity at 40°C (104°F)  | 138 cSt  | 138 cSt  | ASTM D445                   |
| Kinematic Viscosity at 100°C (212°F) | 15.4 cSt | 15.4 cSt | ASTM D445                   |
| Ash                                  | 2.0 %    | 2.0 %    | Sulfated Ash wt%            |

| Thermal Properties | Metric   | English  | Comments |
|--------------------|----------|----------|----------|
| Pour Point         | -27.0 °C | -16.6 °F | ASTM D97 |
| Flash Point        | 252 °C   | 486 °F   | ASTM D92 |

| Component Elements Properties | Metric | English | Comments |  |
|-------------------------------|--------|---------|----------|--|
|-------------------------------|--------|---------|----------|--|



| Component Elements Properties | Metric | English | Comments |  |
|-------------------------------|--------|---------|----------|--|
| Chemical Properties           | Metric | English | Comments |  |
|                               |        |         |          |  |

## **Contact Songhan Plastic Technology Co.,Ltd.**

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058

Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China