

ChevronTexaco Dura-Lith® NLGI 00 Grease EP

Category : Fluid , Lubricant , Lithium Gellant

Material Notes:

FeaturesChevron Dura-Lith Greases EP are multipurpose extreme pressure greases.They are manufactured using selected highly refined medium viscosity index base oils, a lithium 12-hydroxystearate thickener, an extreme pressure additive, and rust and oxidation inhibitors.NLGI 000 is red in color and stringy in texture. NLGI 00, 00, 0, 1 and 2 are amber in color and buttery in texture.Chevron Dura-Lith Greases EP have high load-carrying capacity and, therefore, provide good protection of lubricated parts against wear. They provide excellent lubrication in the presence of water, protect bearing surfaces against corrosion, and have excellent resistance to oxidation, which ensures long life in storage and in use. They are work stable. They resist separation or throw out from antifriction bearings. They have low oil bleeding tendency under pressure and are pumpable at low temperatures.**Applications**Chevron Dura-Lith Greases EP are widely accepted by the industry for use in centralized lubrication systems. NLGI 00, 0, and 1 are recommended for this service. Chevron Dura-Lith Greases EP can satisfy most industrial grease applications. Typical applications are:Plain and antifriction bearingsChassis lubricationConstruction equipmentConveyors and run-out rollsCrusher, shaker, or classifier screen bearingsGeneral machinery lubricationLow and high speed plain bearingsPressesRoller and needle bearingsUnderground mining equipmentNon-disc brake wheel bearingsWinchesChevron Dura-Lith Greases EP are recommended for both plain and antifriction bearings and particularly for bearings subjected to shock loading. Grades NLGI 1 and 2 comply with Timkens recommendation for this service. NLGI 000 is a semifluid grease formulated to meet the lubrication requirements of underground mining machinery having enclosed gear cases where housings and seals have lost their ability to retain conventional gear oils. NLGI 2 grade is approved for the NLGI Certification Mark LB. NLGI grades 0, 1 and 2 are registered with NSF and are acceptable as a lubricant where there is no possibility of food contact (H2) in and around food processing areas. The NSF Nonfood Compounds Registration Program is a continuation of the USDA product approval and listing program, which is based on meeting regulatory requirements of appropriate use, ingredient review and labeling verification.

Order this product through the following link:

http://www.lookpolymers.com/polymer_ChevronTexaco-Dura-Lith-NLGI-00-Grease-EP.php

Physical Properties	Metric	English	Comments
Viscosity Measurement	49	49	Viscosity Index; ASTM D2270
Saybolt Viscosity at 100°F	595 SUS	595 SUS	
Saybolt Viscosity at 210°F	60 SUS	60 SUS	
Kinematic Viscosity at 40°C (104°F)	112 cSt	112 cSt	ASTM D445
Kinematic Viscosity at 100°C (212°F)	9.8 cSt	9.8 cSt	ASTM D445

Mechanical Properties	Metric	English	Comments
Penetration	415	415	Worked
Penetration P(0), 1/10 mm	415	415	
Timken Test	18100 g	40.0 lb	

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	77.0 °C	171 °F	
Minimum Service Temperature, Air	-35.0 °C	-31.0 °F	
Pour Point	-24.0 °C	-11.2 °F	ASTM D97
Flash Point	204 °C	399 °F	ASTM D92
Dropping Point	160 °C	320 °F	

Descriptive Properties	Value	Comments
Color	Amber	
Lincoln Ventmeter, psig at 30 s, at 0°F	125	
Lincoln Ventmeter, psig at 30 s, at -22°F	200	
Texture	Buttery	
Thickener, % / type	2.3 / Lithium	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China