

## ChevronTexaco ECO® ISO 46 Hydraulic Oil AW

Category : Fluid , Lubricant

**Material Notes:**

**Features**Chevron ECO Hydraulic Oils AW are environmentally responsible hydraulic oils.They are manufactured from high viscosity index re-refined paraffinic base oils.They provide antiwear protection, corrosion resistance, oxidation inhibition, and foam suppression for maximum protection in motors and hydraulic systems.**Applications**Chevron ECO Hydraulic Oils AW:are recommended for vane, gear, and piston type hydraulic pumps operating over 1000 psi.are recommended for all types of hydraulic pumps operating at lower than 1000 psi.can be widely used in machine tools, presses, die casting equipment, plastic injection molding machines, circulating systems, and hydraulic control systems.can be used in the lubrication of plain and antifriction bearings, air line lubricators, reciprocating air compressors, and moderately loaded gear sets.

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_ChevronTexaco-ECO-ISO-46-Hydraulic-Oil-AW.php](http://www.lookpolymers.com/polymer_ChevronTexaco-ECO-ISO-46-Hydraulic-Oil-AW.php)

Physical Properties	Metric	English	Comments
API Gravity	31 °	31 °	
Viscosity Measurement	97	97	Viscosity Index; ASTM D2270
Saybolt Viscosity at 100°F	237 SUS	237 SUS	
Saybolt Viscosity at 210°F	48.7 SUS	48.7 SUS	
Kinematic Viscosity at 40°C (104°F)	46 cSt	46 cSt	ASTM D445
Kinematic Viscosity at 100°C (212°F)	6.7 cSt	6.7 cSt	ASTM D445

Thermal Properties	Metric	English	Comments
Pour Point	-15.0 °C	5.00 °F	ASTM D97
Flash Point	210 °C	410 °F	ASTM D92

Descriptive Properties	Value	Comments
Re-refined Oil Content, % of Base Oil	100	

## Contact Songhan Plastic Technology Co.,Ltd.

Website : [www.lookpolymers.com](http://www.lookpolymers.com)Email : [sales@lookpolymers.com](mailto:sales@lookpolymers.com)

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China