

ChevronTexaco Extra Cutting Oil

Category: Fluid, Lubricant

Material Notes:

Texaco Extra Cutting Oil delivers value through: Excellent metal wetting and lubricity properties that allow the oil to spread rapidly on the metal surface and reduce friction and the chip-tool interface. Excellent Surface finish — High fatty oil content allows Texaco Extra Cutting Oil to produce a high surface finish on worked pieces. Use with other cutting oils — Adding Texaco Extra Cutting Oil to other cutting oils enhances their lubricity properties and produces improved surface finish. Non staining for both ferrous and nonferrous metals. Typical test data are average values only. Minor variations which do not affect product performance are to be expected in normal manufacturing. CPS Number: 220723; MSDS Number: 8984

Order this product through the following link:

http://www.lookpolymers.com/polymer_ChevronTexaco-Extra-Cutting-Oil.php

Physical Properties	Metric	English	Comments
API Gravity	22.7°	22.7°	
Viscosity Measurement	114	114	Viscosity Index
Saybolt Viscosity at 100°F	179 SUS	179 SUS	
Saybolt Viscosity at 210°F	47 SUS	47 SUS	
Kinematic Viscosity at 40°C (104°F)	38.3 cSt	38.3 cSt	
Kinematic Viscosity at 100°C (212°F)	6.3 cSt	6.3 cSt	

Thermal Properties	Metric	English	Comments
Flash Point	182 °C	360 °F	

Descriptive Properties	Value	Comments
Fatty Oil wt %	40	

Contact Songhan Plastic Technology Co.,Ltd.

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058

Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China