

ChevronTexaco FM ISO 460 Lubricating Oil

Category : Fluid , Lubricant

Material Notes:

Chevron Lubricating Oils FM are premium performance industrial lubricants designed for use in the food processing and other sensitive industries where incidental food contact may occur. Chevron Lubricating Oils FM provide performance well above that found in typical white mineral oils often used in the food industry. They contain a special biocide to prevent growth of molds when the product comes in contact with food or water. Applications Gear sets rotary steamers valves up to 175°C (350°F)

Order this product through the following link:

http://www.lookpolymers.com/polymer_ChevronTexaco-FM-ISO-460-Lubricating-Oil.php

Physical Properties	Metric	English	Comments
API Gravity	29.2 °	29.2 °	
Viscosity Measurement	118	118	Viscosity Index; ASTM D2270
Saybolt Viscosity at 100°F	2308 SUS	2308 SUS	
Saybolt Viscosity at 210°F	169 SUS	169 SUS	
Kinematic Viscosity at 40°C (104°F)	437 cSt	437 cSt	ASTM D445
Kinematic Viscosity at 100°C (212°F)	34.7 cSt	34.7 cSt	ASTM D445

Mechanical Properties	Metric	English	Comments
Four Ball Wear	0.430 mm	0.0169 in	

Thermal Properties	Metric	English	Comments
Pour Point	-9.00 °C	15.8 °F	ASTM D97
Flash Point	243 °C	469 °F	ASTM D92

Descriptive Properties	Value	Comments
Rust preventative Test Procedure B	Pass	Synthetic Sea Water

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China