

ChevronTexaco Geotex® Ashless SAE 15W-40

Category: Fluid, Lubricant

Material Notes:

Texaco Geotex Ashless is a high quality, bright stock-free, ashless, dispersant-type gas engine oil. It is manufactured using selected paraffinic base oils and an additive package containing a dispersant, wear inhibitor and oxidation inhibitor. Typical test data are average values only. Minor variations which do not affect product performance are to be expected in normal manufacturing. CPS Number: 221879; MSDS Number: 8677

Order this product through the following link:

http://www.lookpolymers.com/polymer_ChevronTexaco-Geotex-Ashless-SAE-15W-40.php

Physical Properties	Metric	English	Comments
API Gravity	30.2°	30.2°	
Viscosity Measurement	127	127	Viscosity Index
Kinematic Viscosity at 40°C (104°F)	104 cSt	104 cSt	
Kinematic Viscosity at 100°C (212°F)	13.4 cSt	13.4 cSt	

Thermal Properties	Metric	English	Comments
Pour Point	-27.0 °C	-16.6 °F	
Flash Point	250 °C	482 °F	

Component Elements Properties	Metric	English	Comments
Phosphorous, P	0.087 %	0.087 %	
Zinc, Zn	<= 0.0010 %	<= 0.0010 %	

Chemical Properties	Metric	English	Comments
Acid Value	0.30	0.30	ASTM D 664
Total Base Number	1.5	1.5	ASTM D2896

Contact Songhan Plastic Technology Co.,Ltd.

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058

Skype: lookpolymers



Address: United North Road 215, Fengxian District, Shanghai City, China