

ChevronTexaco Geotex® Ashless SAE 30

Category : Fluid , Lubricant

Material Notes:

Texaco Geotex Ashless oils deliver value through: Low maintenance cost and long engine life No ash deposits — Eliminates spark plug fouling due to lubricating oil ash deposits. Minimizes deposits on valves, piston heads, combustion chamber surfaces, spark plugs, and port surfaces, reducing the risk of pre-ignition and detonation. Low ring and cylinder liner wear Exceptional engine cleanliness — Minimizes engine deposits at both high and low operating temperatures through the use of ashless dispersant technology. Minimum viscosity increase in severe service. Ashless oxidation inhibitor minimizes viscosity increase allowing for longer oil drain intervals. Excellent copper-lead bearing protection — No corrosion even on bearings without lead or tin overlays. Ability to minimize port deposits in two-stroke engines. Proven performance in older four-stroke naturally aspirated and turbocharged engines. Texaco Geotex Ashless oils are superior quality, ashless, gas engine oils. They are formulated with high quality base stocks and a carefully balanced ashless package of dispersant, antioxidant, extreme pressure, and corrosion inhibitor additives. They are formulated without bright stock for all two-stroke and selected four-stroke high speed, high output, turbocharged, natural gas engines operating at full capacity. Texaco Geotex Ashless oils provide exceptionally clean engine parts, even under severe operating conditions and extended overhaul intervals. They effectively eliminate the formation of crankcase sludge and maintain clean intake and exhaust ports in two-stroke engines. Texaco Geotex Ashless oils eliminate serious problems encountered with ash-containing oils, such as spark plug fouling, pre-ignition, valve guttering, or burning. They reduce wear of piston rings and cylinder liners, and protect against corrosion of vital engine parts. Texaco Geotex Ashless oils are recommended for all two-stroke and selected four-stroke stationary engines that require a completely ashless-type engine oil and which use natural gas or synthetic natural gas as a fuel. They are the preferred products for two- and four stroke engines that are sensitive to combustion chamber and port deposits. They are also recommended for engines with bearing corrosion problems. Texaco Geotex Ashless oils are recommended for engines manufactured by: Ajax Caterpillar (except 3400, 3500, 3600) Clark-Dresser Cooper Bessemer (two-stroke) Dresser-Rand (Ingersoll-Rand) Categories I and II Fairbanks-Morse/MEP Waukesha VR and Intermediate/Clinton Worthington (two-stroke) Texaco Geotex Ashless SAE 30 is suitable for engines manufactured by Dresser-Rand, Categories I and II. Typical test data are average values only. Minor variations which do not affect product performance are to be expected in normal manufacturing. CPS Number: 221877; MSDS Number: 8677

Order this product through the following link:

http://www.lookpolymers.com/polymer_ChevronTexaco-Geotex-Ashless-SAE-30.php

Physical Properties	Metric	English	Comments
API Gravity	30.7 °	30.7 °	
Viscosity Measurement	95	95	Viscosity Index
Kinematic Viscosity at 40°C (104°F)	104 cSt	104 cSt	
Kinematic Viscosity at 100°C (212°F)	11.4 cSt	11.4 cSt	

Thermal Properties	Metric	English	Comments
Pour Point	-24.0 °C	-11.2 °F	
Flash Point	252 °C	486 °F	

Thermal Properties	Metric	English	Comments
Component Elements Properties	Metric	English	Comments
Phosphorous, P	0.067 %	0.067 %	
Zinc, Zn	<= 0.0010 %	<= 0.0010 %	

Chemical Properties	Metric	English	Comments
Acid Value	1.0	1.0	ASTM D 664
Total Base Number	3.1	3.1	ASTM D2896

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China