

ChevronTexaco Geotex® LA SAE 15W-40

Category : Fluid , Lubricant

Material Notes:

Texaco Geotex LA oils deliver value through: Low maintenance cost and long engine life. Low wear — Provide excellent protection against piston, ring, and liner scuffing, scoring, and wear. Reduced valve recession — The level and type of ash producing additives in the oils provide minimum valve recession with low levels of combustion chamber deposits to minimize the potential for pre-ignition and spark plug fouling. Minimum oil viscosity increase — Oxidation inhibited and nitration resistant to insure minimum viscosity increase, long service life, and low wear rates. Cleaner pistons — API CD1 /CF performance provide superior piston cleanliness to prevent ring sticking and maintain clean, varnish-free piston skirts. Clean crankcases and top decks — Minimize the formation of sludge in the crankcase and in the valve rocker cover/top deck area. Catalyst compatibility — Low phosphorous content means compatibility with NSCR emission reduction systems. Improved low temperature performance — Texaco Geotex LA SAE 15W-40 provides increased oil flow to engine components for better lubrication during cold startup; and is suitable for use in selected automotive natural gas engine applications. Texaco Geotex LA oils are high quality, bright stockfree, low ash, dispersant/detergent type engine oils. They are formulated with high quality base stocks and an additive package containing an ashless dispersant, oxidation inhibitors, metallic detergents, and a metallic antiwear agent. Texaco Geotex LA oils provide outstanding oxidation and nitration resistance, which reduce the buildup of insolubles and provide extended oil and filter life. Texaco Geotex LA oils give excellent protection against ring and liner scuffing and wear. They also minimize valve recession in four-stroke engines and provide excellent piston and ring belt deposit control and effectively protect against the formation and buildup of engine sludge. Texaco Geotex LA SAE 15W-40 provides easier engine startup and better oil flow in low temperature conditions. In addition, reduced oil consumption can be achieved, especially in four-stroke engines. Texaco Geotex LA oils are recommended for fourstroke and selected two-stroke stationary engines fueled by natural or synthetic gas and gas from digester and landfill sources. Recommended for four-stroke engines manufactured by: Caterpillar, Delaval, Enterprise, Dresser-Rand Categories I, II, and III (SAE 30). Superior Waukesha, Worthington. Satisfactory for selected two-stroke engines manufactured by: Ajax, Clark-Dresser, Fairbanks-Morse, MEP, Worthington. Texaco Geotex LA oils are formulated to meet NSCR catalyst compatibility requirements and are especially suited for installations requiring low phosphorus oil to prevent exhaust catalyst poisoning. Texaco Geotex LA oils are suitable for use with fuels containing low levels of sulfur and Chloro-Fluoro- Carbons (CFC). In sour gas/high CFC applications, an oil with higher base reserve may be required. Texaco Geotex LA oils SAE 30 and 40 are formulated to meet the performance requirements of API Service Category CD1/CF. Texaco Geotex LA SAE 15W-40 is particularly suited for four-stroke and selected two-stroke gas engines requiring good low temperature startability. Texaco Geotex LA SAE 15W-40 is recommended for use in selected alternate fueled vehicles - mass transit vehicles and local delivery trucks operating on compressed natural gas (CNG), liquefied petroleum gas (LPG), or liquefied natural gas (LNG). Texaco Geotex LA SAE 15W-40 meets the performance requirements of Cummins L10, M11, and Detroit Diesel Series 50G engines running on compressed natural gas. Typical test data are average values only. Minor variations which do not affect product performance are to be expected in normal manufacturing. Notes 1. Obsolete Specification. CPS Number: 222027; MSDS Number: 8917

Order this product through the following link:

http://www.lookpolymers.com/polymer_ChevronTexaco-Geotex-LA-SAE-15W-40.php

Physical Properties	Metric	English	Comments
API Gravity	30.5 °	30.5 °	
Viscosity	3150 cP	3150 cP	Cold Crank

Physical Properties	@Temperature -15.0 °C Metric	@Temperature 5.00 °F English	Comments
Viscosity Measurement	124	124	Viscosity Index
Kinematic Viscosity at 40°C (104°F)	118 cSt	118 cSt	
Kinematic Viscosity at 100°C (212°F)	14.4 cSt	14.4 cSt	
Ash	0.50 %	0.50 %	Sulfated Ash

Thermal Properties	Metric	English	Comments
Pour Point	-27.0 °C	-16.6 °F	
Flash Point	220 °C	428 °F	

Component Elements Properties	Metric	English	Comments
Phosphorous, P	0.027 %	0.027 %	
Zinc, Zn	0.032 %	0.032 %	

Chemical Properties	Metric	English	Comments
Acid Value	1.0	1.0	ASTM D 664
Total Base Number	4.2	4.2	ASTM D2896

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China