

ChevronTexaco Grade 11 Utility Oil HVI

Category : Fluid , Lubricant

Material Notes:

FeaturesChevron Utility Oil HVI is a high quality, high viscosity index un compounded oil with excellent water separating characteristics. Chevron Utility Oil HVI possesses good natural thermal and oxidation stability. Its high viscosity index makes it suitable for use over a wide temperature range. In a circulating oil system, compressor, or lightly loaded gear case, it will maintain a high film strength, protecting metal parts. Lubricant-related deposits will be kept to a minimum due to the excellent stability of this oil. System contaminants such as dirt and moisture can be easily removed from this oil by proper filtration. Chevron Utility Oil HVI ISO 68 is registered with NSF and is acceptable as a lubricant where there is no possibility of food contact (H2) in and around food processing areas. The NSF Nonfood Compounds Registration Program is a continuation of the USDA product approval and listing program, which is based on meeting regulatory requirements of appropriate use, ingredient review and labeling verification.

ApplicationsChevron Utility Oil HVI is recommended: for use in many circulating oil systems* as a cylinder lubricant in double-acting reciprocating compressors for the lubrication of both cylinders and running gears of single-acting compressors for flushing lubricant systems, because of its compatibility for hand oiling Do not use Chevron Utility Oil HVI ISO 68 in high pressure systems in the vicinity of flames, sparks and hot surfaces. Use only in well ventilated areas. Keep container closed.

Order this product through the following link:

http://www.lookpolymers.com/polymer_ChevronTexaco-Grade-11-Utility-Oil-HVI.php

Physical Properties	Metric	English	Comments
API Gravity	34 °	34 °	
Viscosity Measurement	80	80	Viscosity Index; ASTM D2270
Saybolt Viscosity at 100°F	70 SUS	70 SUS	
Saybolt Viscosity at 210°F	36.1 SUS	36.1 SUS	
Kinematic Viscosity at 40°C (104°F)	12.1 cSt	12.1 cSt	ASTM D445
Kinematic Viscosity at 100°C (212°F)	2.9 cSt	2.9 cSt	ASTM D445

Thermal Properties	Metric	English	Comments
Pour Point	-40.0 °C	-40.0 °F	ASTM D97
Flammability Test	204	204	Fire Point °C
Flash Point	179 °C	354 °F	ASTM D92

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China